



Seamless Stainless Steel Metal Tube Pipe 316L SUS304 304L 6.35 Od A269 TP347

Our Product Introduction

for more products please visit us on metalsstainless-steel.com

Basic Information

- Place of Origin: china
- Brand Name: ShengQuan
- Certification: ISO9001:2000
- Model Number: 201/304/304L/316/316L/321/309/310/32750/32760/90
- Minimum Order Quantity: 1ton
- Price: USD1500-USD6000
- Packaging Details: Standard Export Sea-Worthy Packing
- Delivery Time: 5-15days
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 15000Tons



Product Specification

- Width: Or As Required
- Type: Plate, Coil, stainless Steel Sheet
- Standard: ASTM, JIS, AISI, EN, GB
- Length: Customer's Request
- Grade: 201/202/304
/304L/316/316L/321/310s/410/420/430/440/430
- Product Name: ASTM JIS SUS 201 202 301 304 304L 316
316L 310 Stainless Steel Sheet
- Thickness: 0.3mm-120mm, 0.18-1.5mm, 0.2-60mm, 0.45-5mm, 0.01-200mm
- Certification: ISO, SGS, Other
- Technique: Cold Rolled Hot Rolled
- Highlight: **SUS304 Stainless Steel Metal Tube,
TP347 Stainless Steel Metal Tube,
A269 seamless stainless steel pipe**



Product Description

SUS AISI ASTM Stainless Steel Tubing 316 316L 304 304L 6.35 Od Astm A269 1 Polished Stainless Steel Tubing 316I Tp347

Classification of Pipe vs Tubing

Pipes are classified according to their nominal and schedule diameter. Pipe is normally ordered in accordance with the Nominal Pipe Size (NPS) standard, with a schedule number specified (wall thickness) and nominal diameter (pipe size). The schedule number on different sizes of pipe may be the same, but the true wall thickness will differ.

Tubes are usually ordered by wall thickness and outside diameter, but they can also be ordered by outside diameter & inside diameter or inside diameter and wall thickness. A gauge number specifies the thickness of a tube. The interior diameter (ID) is a theoretical measurement.

Tubes can be square, rectangular, or cylindrical in shape, whereas pipe is always round. The circular form of the pipe distributes the pressure load evenly. Pipes are used for larger purposes and come in sizes ranging from 12 inches to several feet. Tubing is typically utilized in applications that demand smaller sizes.

UNS	ASTM	EN	JIS	C%	Mn%	P%	S%	Si %	Cr%	Ni%	Mo %
S20100	201	1.4372	SUS201	≤0.15	5.5-7.5	≤0.06	≤0.03	≤1.00	16.0-18.0	3.5-5.5	-
S20200	202	1.4373	SUS202	≤0.15	7.5-10.0	≤0.06	≤0.03	≤1.00	17.0-19.0	4.0-6.0	-
S30100	301	1.4319	SUS301	≤0.15	≤2.00	≤0.045	≤0.03	≤1.00	16.0-18.0	6.0-8.0	-
S30400	304	1.4301	SUS304	≤0.08	≤2.00	≤0.045	≤0.03	≤0.75	18.0-20.0	8.0-10.5	-
S30403	304L	1.4306	SUS304L	≤0.03	≤2.00	≤0.045	≤0.03	≤0.75	18.0-20.0	8.0-12.0	-
S30908	309S	1.4833	SUS309S	≤0.08	≤2.00	≤0.045	≤0.03	≤0.75	22.0-24.0	12.0-15.0	-
S31008	310S	1.4845	SUS310S	≤0.08	≤2.00	≤0.045	≤0.03	≤1.50	24.0-26.0	19.0-22.0	-
S31600	316	1.4401	SUS316	≤0.08	≤2.00	≤0.045	≤0.03	≤0.75	16.0-18.0	10.0-14.0	2.0-3.0
S31603	316L	1.4404	SUS316L	≤0.03	≤2.00	≤0.045	≤0.03	≤0.75	16.0-18.0	10.0-14.0	2.0-3.0
S31703	317L	1.4438	SUS317L	≤0.03	≤2.00	≤0.045	≤0.03	≤0.75	18.0-20.0	11.0-15.0	3.0-4.0
S32100	321	1.4541	SUS321	≤0.08	≤2.00	≤0.045	≤0.03	≤0.75	17.0-19.0	9.0-12.0	-
S34700	347	1.4550	SUS347	≤0.08	≤2.00	≤0.045	≤0.03	≤0.75	17.0-19.0	9.0-13.0	-
S40500	405	1.4002	SUS405	≤0.08	≤1.00	≤0.04	≤0.03	≤1.00	11.5-14.5	≤0.60	-
S40900	409	1.4512	SUS409	≤0.08	≤1.00	≤0.045	≤0.03	≤1.00	10.5-11.75	≤0.50	-
S43000	430	1.4016	SUS430	≤0.12	≤1.00	≤0.040	≤0.03	≤0.75	16.0-18.0	≤0.60	-
S43400	434	1.4113	SUS434	≤0.12	≤1.00	≤0.040	≤0.03	≤1.00	16.0-18.0	-	-
S44400	444	1.4521	SUS444L	≤0.025	≤1.00	≤0.045	≤0.03	≤1.00	17.5-19.5	≤1.00	-
S40300	403	-	SUS403	≤0.15	5.5-7.5	≤0.04	≤0.03	≤0.50	11.5-13.0	≤0.60	-
S41000	410	1.4006	SUS410	≤0.15	≤1.00	≤0.035	≤0.03	≤1.00	11.5-13.5	≤0.60	≤1.00

S42000	420	1.4021	SUS420J1	0.16~0.25	≤1.00	≤0.04	≤0.03	≤1.00	12.0-14.0	≤0.75	≤1.00
S440A	440A	1.4028	SUS440A	0.60~0.75	≤1.00	≤0.04	≤0.03	≤1.00	16.0-18.0	-	≤0.75
S32750	SAD2507	1.4410		≤0.03	≤1.2	≤0.035	≤0.02	≤0.80	24.0-26.0	6.0-8.0	3.0-5.0
S31803	SAF2205	1.4462		≤0.03	≤2.0	≤0.03	≤0.02	≤1.00	21.0-23.0	4.0-6.5	2.5-3.5
N08904	904L	1.4539		≤0.03	≤2.0	≤0.035	≤0.03	≤1.00	18.0-20.0	23.0-25.0	3.0-4.0





Packing & Delivery

1. Who are we?

We are based in wuxi, China, start from 2021, sell to Mid East(35.00%), South America(20.00%), Southeast Asia(20.00%), Africa(5.00%), Eastern Asia(5.00%), Northern Europe(5.00%), Southern Europe(5.00%), South Asia(5.00%). There are total about 51-100 people in our office.

2. How can we guarantee quality?

Always a pre-production sample before mass production;
Always final Inspection before shipment;

3. What can you buy from us?

steel sheet coil, ppgi ppgl, galvanized steel coil, aluminum steel coil sheet, stainless steel

4. Why should you buy from us not from other suppliers?

Integrating the superior resources of China's steel industry, we provide customers with high-quality steel products at preferential prices, and can ensure that the goods are delivered to customers in a timely manner.

5. What services can we provide?

Accepted Delivery Terms: FOB, CFR, CIF, EXW, FCA, DDP, DDU, Express Delivery

Accepted Payment Currency: USD, EUR, CNY;

Accepted Payment Type: T/T, L/C, Credit Card, Weste



Wuxi Shengquan Metal Products Co., Ltd.



15370898866



523639146@qq.com



metalsstainless-steel.com

Intersection of Xigang Road and Chuntang Road, Xishan District, Wuxi City